SHOWER AND EXPERIENCE SHOWER BREEZE

MODEL	SHOWER AND BREEZE		
CEILING FITTING SIZE (cm)	30 x 30	O	
TECHNOLOGY	Ceiling-mounted plate in stainless-steel, 30 x 30 cm. Shower nozzles integrated into the plate. Breeze nozzles integrated into the plate used also as courtesy lights. no. 1 wall silk-screened plate in stainless-steel. no. 1 lighted piezoelectric button. Distribution hydraulic collector. Electronic valves. Electronic control unit. no. 1 dosing pumps for aromatic essences. no. 1 - 5 l drum of aromatic essences.	٥	
WATER TEMPERATURE	Cold - hot.		
ESSENTIAL OIL	no. 2 - 5 l drum of balsamic.		
LED COLOUR WHEN ON	Blue.		
LED COLOUR WHEN IN STAND-BY	White.		
CYCLE TIMING	12 seconds.		
ABSORPTION	0,15 kW		
WATER PRESSURE AND CONSUMPTION SHOWER	3 bar - 14,0 L/min (4 bar - 16,6 L/min)		
WATER PRESSURE AND CONS. BREEZE	3 bar - 4,2 L/min (4 bar - 5,0 L/min)		

0

0

 \odot